



# L & M COMPRESSOR

Grizzly G520 Five-Stage High Pressure Compressor



## Standard Features

Five Stages

Latest technology in valve and ring design

Spin-on Type Oil Filter

Pressurized oil lubrication system

Cast Iron Block and Cylinders

Designed and built in the USA

Relief Valves on 1st, 2nd, 3rd & 4th Stage

Connecting rods with needle roller bearings

Stainless steel valve assemblies on all stages

Radial layout for reduced vibration and crank shaft loading

Intercoolers on 1st, 2nd, 3rd & 4th, after cooler on 5th stage

Water separators on 2nd, 3rd & 4th stages

Benefits of Low  
RPM Technology

Long Life

Low Noise

High Efficiency with Reduced Heat



5 Cylinder, 5 Stage Breathing Air Compressor

Model	Max Working Pressure		Capacity (1)		Motor	
	psig	bar	scfm	l/min	hp	Kw
G515-6	6,000	414	18	510	15	11
G520-6	6,000	414	24	680	20	15
G525-6	6,000	414	29	821	25	18.5

5 Cylinder, 5 Stage Breathing Air Compressor

Model	Max Working Pressure		Capacity (1)		Motor	
	psig	bar	scfm	l/min	hp	Kw
G515-7	7,500	517	17.5	496	15	11
G520-7	7,500	517	23.5	665	20	15

1) Capacity is referenced to standard inlet conditions (ASME Standard) @ 80% of the compressor's maximum working pressure. Tolerance +5/-4%

2) Specifications are subject to change.

### Dimensions

Width	36" (Side to Side)
Depth	24" (Front to Back)
Height	36"
Weight	460 Lbs.
Fan Diameter	29.5"

### Optional Features:

- Oil pressure switch
- Fan Guard
- ACD- Automatic Drain Block with Solenoid